



## 1) LOW TEMPERATURE FREEZER VTS 230

LOW TEMPERATURE FREEZER	TECHNICAL DATA												
<p><u>VTS 230</u></p>  <p><u>INTERIOR</u></p>  <p><u>CASTORS</u></p>  <p><u>USB</u></p> 	<p><u>LOW TEMPERATURE FREEZER VTS 230</u></p> <table border="1"><thead><tr><th>DIMENSIONS</th><th>D</th><th>W</th><th>H</th></tr><tr><th>[MM]</th><th>EXTERNAL</th><th></th><th></th></tr></thead><tbody><tr><td></td><td><b>643</b></td><td><b>600</b></td><td><b>2055</b></td></tr></tbody></table> <p><b>Capacity:</b> 234/217 [L] <b>Weight:</b> 116/125 [kg] <b>Shelves:</b> 5 pc. <b>Temperature:</b> -60... -86 [°C] <b>Ambient temp. range:</b> +16... +20 [°C] przy 60% HR <b>Power:</b> 230/50 [V/Hz] <b>Outside doors:</b> 1 pc. <b>Nosie level:</b> 60 [dB]</p> <p><b>VERSION:</b></p> <ul style="list-style-type: none"><li>Single compressor</li><li>Digital display</li><li>Digital kontroler DIXELL NG+</li><li>Power failure alarm</li><li>Battery backup (in case of power cut) 48h- optional</li><li>Optional chart recorder</li><li>Data logger</li><li>USB data transfer</li><li>Lighting</li><li>Adjustable shelves plate 5pc.</li><li>Inner lids: 2 pc.</li><li>Handle</li><li>Castors</li><li>Lock</li><li>Open door/ lid alarm</li><li>Probe failure alarm</li><li>Visual&amp; acoustic alarm</li><li>Exterior color white</li><li>Material outside: galvanized steel</li><li>Material inside: stainless steel</li><li>Model available in two temperatures: 86 ° C, 45 ° C</li></ul> <p><b>STANDARD EQUIPMENT:</b></p> <ul style="list-style-type: none"><li>Manual</li><li>Warranty book with a list of service centers</li></ul>  <p><u>CONTROL PANEL</u></p>	DIMENSIONS	D	W	H	[MM]	EXTERNAL				<b>643</b>	<b>600</b>	<b>2055</b>
DIMENSIONS	D	W	H										
[MM]	EXTERNAL												
	<b>643</b>	<b>600</b>	<b>2055</b>										

